

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20160419-E211115  
**Report Reference** E211115-A11-UL  
**Issue Date** 2016-APRIL-19

**Issued to:** N2Power, Division of Qualstar  
130-C W COCHRAN ST  
SIMI VALLEY CA 93065

**This is to certify that  
representative samples of**

Power Supplies for Information Technology Equipment  
Including Electrical Business Equipment  
See Addendum

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.

**Standard(s) for Safety:**

UL 60950-1 and CAN/CSA C22.2 No. 60950-1-07, Information  
Technology Equipment - Safety - Part 1: General Requirements

**Additional Information:**

See the UL Online Certifications Directory at  
[www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's  
Certification and Follow-Up Service.

Recognized components are incomplete in certain constructional features or restricted in performance  
capabilities and are intended for use as components of complete equipment submitted for investigation rather  
than for direct separate installation in the field. The final acceptance of the component is dependent upon its  
installation and use in complete equipment submitted to UL LLC.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please  
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20160419-E211115  
**Report Reference** E211115-A11-UL  
**Issue Date** 2016-APRIL-19

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

DC to DC Power Supply: Models

XL125-1DC, XL125-8DC, XL160-1DC, XL160-1DC S117, XL160-8DC, may be followed by optional string of alpha-numeric characters not affecting safety.

XL125-xx-yyDC, XL160-xx-yyDC, where xx can be 05-011 or 12-56 (denotes V1 voltage 5Vdc-56Vdc), may be followed by yy where yy can be 5-12 (denotes V2 voltage 5Vdc-12Vdc, yy omitted for default 12Vdc), may be followed by optional string of alpha-numeric characters not affecting safety



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

